



## BULLOCK ACCESS DOOR



Galvanised - AD509, AD512 & AD515



Galvanised - AD612 & AD615

### PRODUCT DESCRIPTION

Bullock insulated access doors are designed specifically for HVAC plant room conditioner housings. Available in 5 stock sizes these doors provide ample open area access for personnel or maintenance related equipment. Such routine maintenance would include repair to or replacement of: fire, volume, non-return, motorised fire/smoke dampers, conditioner coils and filters, actuators or pumps to Australian Standard procedures.

### PRODUCT SPECIFICATION

- DOOR:** 2 piece 1.2mm galvanised sheet, press formed and welded to make airtight
- FRAME:** 1 piece 2.5mm galvanised steel angle section, with continuously welded corners
- HANDLES:** Die cast zinc un-plated or Chrome
- HINGES:** Chrome plated, die and press formed complete with nylon over stainless steel to prevent seizing
- DOOR SEAL:** 1 piece heat welded extruded PVC compression gasket mechanically fixed within
- INSULATION:** 25mm fibreglass insulation is sealed within the door cavity to prevent cold  
304 Stainless Steel or 316 Stainless Steel

## CUT HOLE SIZES FOR FLUSH MOUNTED ACCESS DOORS \* THIS VARIES FROM SEMI RECESSED ACCESS DOORS \*

25mm CODE	50mm CODE	ITEM - NOMINAL SIZE	DOOR PANEL	CUT HOLE	OUTSIDE FRAME	INSIDE FRAME	NO. OF HANDLES
0505/Galv25mm	0505/Galv50mm	AD509 510	564 x 819	520 x 775	640 x 895	508 x 762	1
0512/Galv25mm	0512/Galv50mm	AD512 510	564 x 1124	520 x 1080	640 x 1200	508 x 1067	2
0515/Galv25mm	0515/Galv50mm	AD515 510	564 x 1428	520 x 1384	640 x 1504	508 x 1372	2
0615/Galv25mm	0615/Galv50mm	AD615 650	704 x 1428	660 x 1384	780 x 1504	648 x 1372	2
0617/Galv25mm	0617/Galv50mm	AD617 650	704 x 1683	660 x 1639	780 x 1759	648 x 1627	2
0505/25mm304SS	0505/50mm304SS	304 S/Steel	564 x 819	520 x 775	640 x 895	508 x 762	1
0512/25mm304SS	0512/50mm304SS	304 S/Steel	564 x 1124	520 x 1080	640 x 1200	508 x 1067	2
0515/25mm304SS	0515/50mm304SS	304 S/Steel	564 x 1428	520 x 1384	640 x 1504	508 x 1372	2
0615/25mm304SS	0615/50mm304SS	304 S/Steel	704 x 1428	660 x 1384	780 x 1504	648 x 1372	2
0617/25mm304SS	0617/50mm304SS	304 S/Steel	704 x 1683	660 x 1639	780 x 1759	648 x 1627	2
0505/25mm304SS	0505/50mm304SS	316 S/Steel	564 x 819	520 x 775	640 x 895	508 x 762	1
0512/25mm304SS	0512/50mm304SS	316 S/Steel	564 x 1124	520 x 1080	640 x 1200	508 x 1067	2
0515/25mm304SS	0515/50mm304SS	316 S/Steel	564 x 1428	520 x 1384	640 x 1504	508 x 1372	2
0615/25mm304SS	0615/50mm304SS	316 S/Steel	704 x 1428	660 x 1384	780 x 1504	648 x 1372	2
0617/25mm304SS	0617/50mm304SS	316 S/Steel	704 x 1683	660 x 1639	780 x 1759	648 x 1627	2

When ordering please use the codes listed.

Your local representative can be located at [www.bullockmfg.com.au](http://www.bullockmfg.com.au)

