



BULLOCK

www.bullockmfg.com.au

GENERAL PURPOSE FLEXIBLE FAN CONNECTOR

GENERAL PURPOSE FABRIC ONLY PRODUCT DESCRIPTION

Bullock general purpose fabric only flexible fan connector is ideal for on site flexible fan connector installations where metal strips in addition to the fabric is not required. Applications such as fume extraction systems, round exhaust systems or minor repairs to existing flexible connections



FEATURES

- **Fabric:** Construction is a heavy duty woven denier polyester 650 T/S tearstop PVC coated tarpaulin material with a weight of 690 gsm (+/- 30gsm)
- **Tensit strength (AS2001.2.3):** WARP - 3320N. WEFT - 2650N.
- **Tongue Tear (BS3424.5):** WARP - 650N. WEFT - 650N.
- **Flex Cracking (AS141.6):** 400,000 Cycles
- **Coating Adhesion:** Unable to be delaminated, abrasion resistant
- **Cold Crack Temperature (CCT):** -30 Degree C
- **U.V. Treated:** Yes
- **Anti-fungicide treated:** Yes
- **Waterproof:** Yes, Acrylic lacquer coated
- **Airtight:** Yes
- **Joining Adhesive:** Use general purpose PVC type adhesives. For high velocity air systems a washer/rivet/washer reinforcing system should be used
- **Colour:** Grey
- **Roll length:** 25 metres
- **Roll widths:** 150mm, 200mm, 250mm

Your local representatives details can be located at www.bullockmfg.com.au



BULLOCK
www.bullockmfg.com.au