



BULLOCK SEMI RECESSED ACCESS DOOR



DIMENSIONS

CUT HOLE SIZES FOR SEMI RECESSED ACCESS DOORS						
* THIS VARIES FROM FLUSH MOUNTED ACCESS DOORS *						
CODE	MODEL	O/ALL SIZE W x H	PLUG SIZE	HOLE SIZE REQUIRED W x H	CLEAR OPENING W x H	DOOR HANDLES
0509-SR	509-SR	766 x 1050	685 x 969	695 x 979	608 x 892	1
0512-SR	512-SR	766 x 1290	685 x 1209	695 x 1219	608 x 1132	2
0515-SR	515-SR	766 x 1490	685 x 1409	695 x 1419	608 x 1332	2
0520/1-SR	520/1-SR	616 x 1216	535 x 1135	545 x 1145	458 x 1058	2
0525-SR	525-SR	661 x 1211	580 x 1130	590 x 1140	503 x 1053	2
0560-SR	560-SR	671 x 1531	590 x 1450	600 x 1460	513 x 1373	2
0565-SR	565-SR	671 x 931	590 x 850	600 x 860	513 x 773	1
0570-SR	570-SR	806 x 2111	725 x 1130	735 x 1140	648 x 1053	2
0610-SR	610-SR	821 x 1806	740 x 1725	750 x 1735	663 x 1648	2
0615-SR	615-SR	766 x 1790	685 x 1709	695 x 1719	608 x 1632	2

CONSTRUCTION DETAILS

- Semi recessed style door
- Prime galvanised steel panels (1.2mm) & frames (2.5mm)
- Heavy duty R40 (chrome plated handle sets) adjustable hinges
- Heavy duty chrome plated handle (optional internal handle chrome plated)
- 10 stock sizes available
- Special sizes made to order
- Powder coating is available

Your local representatives details can be located at www.bullockmfg.com.au

