



BULLOCK

Quality Products for the Air Conditioning Industry

ADELAIDE

(08) 8349 7088

BRISBANE

(07) 3271 2088

MELBOURNE

(03) 9587 5522

SYDNEY

(02) 9684 1311

PERTH

(08) 9248 1633

4900 SERIES CURTAIN BLADE FIRE DAMPER

AUSTRALIAN MADE | CERTIFIED PERFORMANCE | ENGINEERED RELIABILITY

Our fire-rated damper system is designed to deliver exceptional safety, durability, and performance for modern construction projects. Proudly Australian-made, the system is certified to AS 1530.4:2014 (Sections 2 & 11), ensuring proven fire resistance and compliance with stringent building standards.



KEY FEATURES

- AS 1530.4:2014 Certified – Tested to Sections 2 & 11 for reliable fire performance
- Australian-Made Construction – Manufactured using locally sourced galvanized steel
- Bullock's Patented Metal Seals – Ensuring superior reliability and operational efficiency
- UL33 Rated Fusible Fire Link – Provides dependable activation during fire events
- TDF / TDC Channels Standard – With optional angle connections for installation flexibility
- Optional Airflow Feature – Available for wall-mounted damper applications

TESTED STRUCTURAL REQUIREMENTS

- Minimum Wall Density: 735 kg/m³
- Minimum Slab Density: 2503 kg/m³
- Verified by Sponsored Reports: FRT210347 , FRT240128 & FAS210293

AVAILABLE SIZES

AAC, CLT, Speedpanel & Masonry Wall Applications

150 mm × 150 mm up to 4800 mm × 4800 mm

Plasterboard Wall Systems

150 mm × 150 mm up to 2400 mm × 2400 mm

Slab Applications


150 mm × 150 mm up to 2000 mm × 1000 mm

Up to 2000 mm × 2000 mm with structural brace

Each slab unit includes two 301 stainless steel Conforce springs, designed to enhance structural stability and long-term performance.

MODELS AVAILABLE

STYLE "D"



Wall
thickness

DUCT - TO - DUCT

For exact dimensions and sizing, please contact your local representative.


Order should read as follows:

Width (blade length) × Height × Wall thickness

Minimum wall thickness = 80mm

· Channel width may increase with small walls Flange

STYLE "G"



Grille Flange

Grille
depth
Wall
thickness

GRILLE - TO - DUCT

Made to internal dimensions

Order should read as follows:

Width (blade length) × Height × Wall thickness × Depth of recess for Grille × Flange

· Channel width may increase with small walls

· Minimum flange size "T" (max W or H / 100) + 10.

· Refer AS1682.2-2012

RECOMMENDED NYLON FIXINGS




8mm Fire Damper Low Melting Point Nylon Bolt

Melting point temp below 200Deg. C

For use with TDF/TDC flange channel connections

Code #4908/2




8mm Nylon TDF clamp

Melting point temp below 200Deg. C

For use with TDF/TDC flange channel connections

Code #1390/1

PRESSURE DROP



WEIGHTS



BUILT FOR VERSATILITY

With a wide range of manufactured sizes and installation options, the system can be tailored to suit both small-scale installations and large architectural projects, providing flexibility without compromising fire safety or compliance.